



Advanced Technology. Simple Solutions.

# PARKING LOT CONTROLLER WITH ENERSAVE LOGIC AND MAIN CONTACTOR

## VPC-DB

The VPC-DB parking lot controller uses Enersave logic to control multiple setpoints for parking lot applications. With a durable finish in standard PC101 Grey powder coat paint, its weatherproof design is ideal for outdoor use. This line of parking lot controllers is all-encompassing with the main contactor and breaker panel located in a single pad-mount enclosure.

### Features / Specifications

- Steel construction
- CSA Type 3R rated
- Padlockable handle
- Enersave temperature controller with:
  - Up to 4 customer-programmable temperature setpoints (recommended -5°C, -10°C, -15°C, -20°C)
  - Duration of cycle
  - Supervisory enable signal
- Easy field configuration via jumper settings
- Standard 120/208V 3-phase
- HOA switch to bypass logic
- Temperature-sensing cable with weatherproof cover
- Main contactor and circuit breaker panel
- Pad-mount design
- PC101 Grey powder coat finish

### Options

- Wall-mounted enclosure
- Higher amperage ratings
- Single-phase (120/240V)
- Time-of-day clock
- Aluminum or stainless steel construction
- CSA type 1, 4, or 4X rated
- Remote-sensing thermostat
- Custom powder coat colours

PART NUMBER	MAIN CONTACTOR	CIRCUITS
VPC-DB-60-12	60A	12
VPC-DB-75-12	75A	12
VPC-DB-90-18	90A	18
VPC-DB-90-30	90A	30
VPC-DB-115-30	115A	30
VPC-DB-150-30	150A	30
VPC-DB-150-42	150A	42
VPC-DB-185-30	185A	30
VPC-DB-185-42	185A	42
VPC-DB-225-30	225A	30
VPC-DB-225-42	225A	42

