



Advanced Technology. Simple Solutions.

VPS 40KWH-12KW BATTERY PACK

Reliable Portable Power • Hybrid Compatible

Electrical

Useable Capacity	40kWh
Nominal Capacity	46kWh
20 Sec Surge Power (5°C to 40°C)	20kW
1 Min Surge Power (5°C to 40°C)	15kW
15 Min Surge Power (5°C to 40°C)	13.5kW
Continuous Output Power (5°C to 40°C)	12kW
Input Voltage	194 to 243 VAC
Output Voltage (Pure Sine Wave)	110/230VAC Split-phase +/- 10%
Level 2 EV Charging	240VAC +/- 5%
Charge Cycles (80% Capacity)	Min 3000
AC Charge Current (Selectable)	15A, 24A, 30A (@ 240VAC)
Charge Time	30A/240VAC = 7.5 hrs

Mechanical

Max Dimensions	39"W x 35"H x 52"L
Max Weight	1150 lb
Transportation	Valid Trailer

Safety Certifications

SPE1000

Environmental

Ambient Temperature Range	Discharge -30°C to 50°C -22°F to 122°F Charge -10°C to 45°C -14°F to 113°F
Humidity	95% non-condensing
IP Rating	54

Input Connections (Multiple Configurations Available)

Twist Lock CS8275 50A @250VAC California-Style

J1772 EV Connector

Output Connections (Multiple Configurations Available)

NEMA 5-20R 20A @ 120VAC

Joy or Bates 50A @ 120VAC

Twist Lock CS8269 50A @ 240VAC

NEMA L5-30R 30A @ 120VAC

Closed-Contact AutoGen Start

USB Fast-Charge Ports

Optional Features

PV Charging

Remote Monitoring



Design and features subject to change